

Nitto tape 15 self-fusing butyl rubber tape



Isolation of constant force springs in cable joints
Incapsulation of cable joints and endconnections
Corrosion protection for repair of cable-isolation
Isolation and watertight sealing of cables and pipes which should be protected against moisture

Rasgos

- Excellent vulcanising properties. When the tape is applied with a stretch of 80%, it will be vulcanized in 1 – 2 hours
- No liner and therefore no wasting time for peeling the liner
- No liner waste material
- Excellent electrical properties. High isolation values and break down voltage
- Excellent weather and water resistance
- Fully resistant against moisture, water, and many chemicals

Nitto tape 15 self-fusing butyl rubber tape

Especificaciones

Material	Self-fusing butylrubber
colour	black
Elongation at break	at least 550% at 23°C
Breakdown voltage	44 kV/mm

Nitto tape 15 self-fusing butyl rubber tape

Más información

<http://www.filoform.nl/en/nitto-tape>

Productos

Art.nr.	Product Naam	Dimensiones	Color	Unidad de embalaje
800452	Self-fusing butylrubbertape 19mm x 5m x 0,75mm	19mm x 5m x 0,75mm	negro	100 rollen /carton
80046	Self-fusing butylrubbertape 38mm x 10m x 0,50mm	38mm x 10m x 0,50mm	negro	50 rollen / carton