

Divisible duct seals 12mm



Filoform divisible duct sealing sets for subducts have been developed to provide an effective and simple solution to all Gas and Watertight duct sealing requirements.

This modular system enables you to install it easily onto new and existing installations. Due to the compact design the seals can be installed in all situations, even in locations with difficult access.

For use on subducts of 12mm.

PATENTED

Rasgos

- Gas and Watertight up to 0,5 bar.
- Suitable for retrofitting.
- Easy installation.
- Slim design.
- Other versions available upon request.

Divisible duct seals 12mm

Especificaciones



Dimensions	A (mm)	B (mm)	Weight (gr.)
Duct seal 12mm	30	24	12

Material specification

Properties	Value
Plastic scales	glassfibre reinforced
Cutting block	glassfibre reinforced
Sealing plug	silicone
Sealing	up to 0,5 bar
Pull-out force duct seal vs duct	≥ 120N
Mechanical compression strength	≥ 1000N, 10 sec.

Más información

Contents

- 2 pieces of plastic shells with click together fixings
- 1 piece cutting block
- 1 rubber seal
- Illustrated installation instructions

Deelbare glasvezel afdichting
Divisible fibre optic seals
Teilbar LWL-dichtungen
Fibre optique divisible sceaux
Sellos de fibra optica

FILOform



Divisible duct seals 12mm

Productos

Art.nr.	Product Naam	Color	Diámetro exterior del conducto (mm)	Diámetro del cable (mm)	Unidad de embalaje
822812.0	Duct seal 12mm / 2,5-1,5mm	violeta	12	2,5-1,5	25 pcs/carton
822812.1	Duct seal 12mm / 3,5-2,5mm	azul claro	12	3,5-2,5	25 pcs/carton
822812.2	Duct seal 12mm / 5,0-3,5mm	verde	12	5,0-3,5	25 pcs/carton
822812.3	Duct seal 12mm / 6,5-5,0mm	rojo	12	6,5-5,0	25 pcs/carton
822812.4	Duct seal 12mm / 8,0-6,5mm	azul oscuro	12	8,0-6,5	25 pcs/carton
822812.5	Duct seal 12mm / 8,5-7,0mm	azul claro	12	8,5-7,0	25 pcs/carton