

Wrap around sleeves



Cable joints and cable terminations
Cables till 1kV
Telecommunication
Indoor / Outdoor underground, above ground, under water, in cable ducts

Rasgos

- Polyolefine cross linked
- Fast recovery
- Continuous temperature -40°C till +125°C
- Excellent resistance against UV and chemicals
- Corrosion resistant
- colour: black

Especificaciones

Material	Polyofine	
Shrink temperature	> 125°C	
Continuous temperature	-40°C till +125°C	
Dielectric strength	≥ 22 kV/mm	ASTM D 149-97a
Volume resistivity	> 1 x 10 ¹⁴ ohm cm	ASTM D 257-98
Heatshock (225°C)	No damage	ASTM D 2671-98
Tensile strength	≥ 18 Mpa	ASTM D 638-98
Elongation at break	≥ 500%	ASTM D 638-98
Waterabsorbtion	≤ 0,5%	ISO 62-86
Mould resistance	No growth	ASTM G21-96 / ASTM D 638-98
Oil resistance	Excellent	ISO 175-99

Wrap around sleeves

Productos

Art.nr.	Product Naam	Espesor después de la contracción (mm)	Unidad de embalaje
44400	Wrap around sleeve 43/8 x 500mm	2,0	per piece
44401	Wrap around sleeve 50/15 x 500mm	2,0	per piece
44411	Wrap around sleeve 105/30 x 600mm	2,0	per piece
44412	Wrap around sleeve 146/38 x 800mm	2,0	per piece