



For the connection of copper or aluminium conductors Suitable on massive and on flexible conductors ETON23 is suitable for conductor diameters from 0,35 till 0,90mm ETON23EN is suitable for conductor diameters from 0,5 till 1,3mm

Rasgos

- Excellent electrical properties, extremely low resistance
- 100% reliable, the conductors can not be damaged
- Excellent protection of the connections against gasses and fluids through pre-lubrication
- Quick and easy connecting, self stripping
- Close with light pressure, without special tools
- Isolation is automatically stripped
- Big contrast area
- High contact pressure
- Fire retardant, gel-filled
- Temperature resistance from -30°C till +100°C
- Visual check possible through the transparent housing
- Double "click" when closing the connector
- High climate resistance
- Internal lubrication ensuring seal and corrosion protection

Especificaciones



	Type connector	Core diameter	Max. current	Application electricity	Application telecom
	23YF	0,35-0,90	6 Amp.	Connection, 2 conductors	Splicing, 2 conductors
	23G	0,40-0,80	6 Amp.	Branch-off without interruption, 2 conductors	Splicing without interruption, 2 conductors
	23	0,35-0,90	6 Amp.	Connection or branch-off, 2 till 5 conductors	Splicing or Y-branch off, 2 till 5 conductors
	23EN	0,50-1,30	30 Amp.	Connection, 2 conductors	Connection of above ground cables, 2 conductors

Productos

Art.nr.	Product Naam	Unidad de embalaje
8802024	Eton connector type 23G blue	100 pcs/carton
8802026	Eton connector type 23EN black	100 pcs/carton