

# Medium wall Shrink tube with glue layer 3:1 & 4:1



Cable joints and cable terminations Cables till  
1kV Telecommunication Indoor / Outdoor underground, above  
ground, under water, in cable ducts

## Rasgos

- Polyolefine crosslinked
- Fast recovery
- Shrink temperature 70°C till 100°C
- Continuous temperature range from -55°C till +90°C
- Good resistance against UV and chemicals
- Corrosion resistant
- Flexible
- Cadmium free and halogen free
- Colour: black

# Medium wall Shrink tube with glue layer 3:1 & 4:1

## Especificaciones

Material	Polyofine	
Shrink temperature	> 125°C	
Continuous temperature	-55°C till +90°C	
Dielectric strength	≥ 15 kV/mm	ASTM D 2671-98
Volume resistivity	> 1 x 10 <sup>12</sup> ohm cm	ASTM D 257-98
Heatshock (30 min/200°C)	No damage	ASTM D 2671-98
Tensile strength	≥ 12 Mpa	ASTM D 2671-98
Elongation at break	≥ 400%	ASTM D 2671-98
Longitudinal change	≤ 15%	ASTM D 2671-98
Waterabsorbtion	≤ 0,5%	ASTM D 570

# Medium wall Shrink tube with glue layer 3:1 & 4:1

## Productos

Art.nr.	Product Naam	Espesor después de la contracción (mm)	Color	Unidad de embalaje
8415040	Shrink tube MW 40/12	2,5	rojo	10 pcs x 1200mm