

# Flat tinned braid



Filoform flat tinned braid is used for making earth connections in cable joints which provide a fault current path across shielded cable joints. In case of a Paper Insulated Lead Sheath Cable (PILC) the flat tinned braid can be connected on to the lead with use of a Filoform constant force spring. For making sustainable earth connections in cable joints For grounding high-voltage joints, terminations and cables

## Rasgos

- Tinned copper wires
- Flexible
- Corrosion resistant
- Suitable for indoor and outdoor use
- Other sizes available on request

## Especificaciones

Nominal mm <sup>2</sup>	Nominal dimensions	Current rating amps
10mm <sup>2</sup>	15mm x 1,5mm	90
25mm <sup>2</sup>	26mm x 1,6mm	150
35mm <sup>2</sup>	25mm x 2,5mm	200

## Productos

Art.nr.	Product Naam	Unidad de embalaje
800194	Flat tinned braid 10mm <sup>2</sup> x 2,4m	50pcs./box
800195	Flat tinned braid 10mm <sup>2</sup> x 0,6m	50pcs./box
800196	Flat tinned braid 25mm <sup>2</sup> x 3,0m	15pcs./box
800197	Flat tinned braid 25mm <sup>2</sup> x 0,6m	50pcs./box
800199	Flat tinned braid 35mm <sup>2</sup> x 0,5m	50pcs./box